

ECSi

"Your Regulatory Compliance Expert"

May 29, 2019

Mr. Ezekiel Rodriguez Facilities Department ABBOTT VASCULAR 26531 Ynez Road Temecula, California 92591

Subject:

RESULTS OF ANNUAL ETHYLENE OXIDE SOURCE TESTING AND LEAK TESTING PERFORMED AT ABBOTT VASCULAR IN TEMECULA, CALIFORNIA

Dear Mr. Rodriguez:

Please find attached a presentation of the results of the ethylene oxide source testing and leak testing performed at your facility by ECSi, on Wednesday, May 29, 2019. These test results are to be kept with all records pertaining to SCAQMD-required testing of the EtO gas-sterilization system, and are to be made available upon request by the SCAQMD. A copy of all raw test data, complete with sample chromatograms and calibration data, will be maintained in our files, and will be made available upon request.

The test results indicate that you continue to operate your EtO sterilization and emission-control system (SCAQMD Permit Numbers F83295 and F83299) in compliance with SCAQMD Rule 1405. I will follow up with you in approximately five months to let you know when your next semi-annual leak test is due, and in approximately eleven months to let you know when your next annual source test/leak test is due.

The annual ethylene oxide emissions reported in Table 2 can be used for your facility's annual SCAQMD emissions report. If you have any questions or comments regarding this submittal, please contact me at (949)400-9145. We thank you for the opportunity to serve your needs.

Respectfully Submitted:

Daniel P. Kremer

ECSi

TABLE 1 ETHYLENE OXIDE CONTROL EFFICIENCY OF AN ETHYLENE OXIDE EMISSION CONTROL DEVICE (ABATOR #2 - F83299) OPERATED BY ABBOTT CARDIOVASCULAR SYSTEMS IN TEMECULA, CALIFORNIA ON MAY 29, 2019

CYCLE PHASE	INJECTION <u>TIME</u>	INLET ETO CONC. (PPM)(1)	OUTLET ETO CONC. (PPM)(2)	ETO CONTROL EFFICIENCY
Exhaust(3)	1229	6390	1.59	99.9751
Exhaust	1231	5860	0.01	99.9998
Exhaust	1233	4850	0.01	99.9998
Exhaust	1235	3760	0.01	99.9997
Exhaust	1237	122	0.01	99.9918
Exhaust	1239	<u>12.3</u>	<u>0.01</u>	<u>99.9187</u>
TIME-WEIGHTED AVERAGE:		3499	0.2733	99.9808

SCAQMD REQUIRED CONTROL EFFICIENCY:

Notes:

- (1) PPM = parts per million by volume
- (2) 0.01 ppm is the quantification limit for the detector used at the outlet.
- (3) The exhaust phase started at 12:27, ended at 12:40.

99.0

TABLE 2 ETHYLENE OXIDE MASS EMISSIONS FROM A GAS STERILIZATION AND EMISSION CONTROL SYSTEM (F83299/F83295) OPERATED BY ABBOTT CARDIOVASCULAR SYSTEMS IN TEMECULA, CALIFORNIA ON MAY 29, 2019

CYCLE PHASE	STACK FLOW(1)	OUTLET ETO MASS FLOW(2)	MINUTES/ CYCLE	CYCLES/ YEAR	ANNUAL ETO MASS EMISSIONS(3)	
Exhaust	47.6 DSCFM	0.00000013 lbs/min	13	60	0.0038 lbs/year	
		TOTAL ANNUA	TOTAL ANNUAL ETO MASS EMISSIONS			

Notes:

- (1) DSCFM = Dry Standard Cubic Feet per Minute
- (2) lbs/min = pounds per minute
- (3) lbs/year = pounds per year

TABLE 3 ETHYLENE OXIDE LEAK TESTING OF A GAS STERILIZATION SYSTEM (F83295) OPERATED BY ABBOTT CARDIOVASCULAR SYSTEMS IN TEMECULA, CALIFORNIA ON MAY 29, 2019

COMPONENT GROUP TESTED	LEAKING COMPONENTS FOUND	CONCENTRATION	
Gas Cartridge / Injector	None	<1.0 ppm (1)	
Sterilizer Inlet / Inbleed Valve	None	<1.0 ppm	
Door Seal	None	<1.0 ppm	
Sterilizer Outlet / Chamber Drain	None	<1.0 ppm	
Venturi System / Filter	None	<1.0 ppm	
Emission Control Device Inlet	None	<1.0 ppm	

Notes:

(1) - PPM = parts per million by volume

ECSi, Inc.
Ethylene Oxide Mass Emissions Data and Calculations

Abbott Vascular, Inc. - Temecula, CA - May 29, 2019 Abator #2 (F83299) - Sterilizer #2 (F83295)

<u>DeltaP</u>	<u>SqRtDeltaP</u>	Temp (F)	ppm EtO	stack ID =	3	in.
				stack area =	0.049	sq. in.
Exhaust Phase				press =	28.65	in. Hg
				Tstd =	528	deg R
0.11	0.3317	329	1.59	Pstd =	29.92	in Hg
0.11	0.3317	336	0.01	Cp =	0.99	•
0.11	0.3317	349	0.01	Kp =	85.49	
0.11	0.3317	401	0.01	-		
0.11	0.3317	476	0.01	Velocity =	29.27	ft/sec
0.11	0.3317	528	0.01	Flow =	47.6	dscfm
0.11	0.3317	576	<u>0.01</u>			
				MWeto =	44.05	
Average =				MolVol =	385.32	
0.1100	0.3317	428	0.2357	ppmv/ft3 =	1000000	
	=	888	degR	EtO Mass Flow (Exh) =	0.0000013	lbs/min
				min/cycle =	50	
				•	60	
				cycles/year =	δU	
				Annual EtO Emissions =	0.0038	lbs/year